

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2 BLACK

PRODUCT CODE  
ŠIFRA PROIZVODA

**230301B**



### TEHNIČKI PODACI

Dvoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Završna obrada - PVD Dark black  
Montiranje na tri otvora  
Klasa protoka Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR® PPM24SA  
Keramički gornji deo  
Set za pričvršćenje  
Prikjučni cev

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Two handle mixer  
Minimalist design  
Solid brass body  
Dark black PVD finish  
Three hole mounted  
Flow rate Z - 7 lit/min  
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA  
Ceramic head parts  
Single screw fixing set  
Connecting hoses

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

