

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

237251B



TEHNIČKI PODACI

Jednoručna baterija

Minimalistički dizajn

Telo od mesinga

Završna obrada - PVD Dark black

Zidna montaža

Keramički prebacivač 180°

Tuš ruža 210x210mm - PTRUSP5D

Keramički mešač CITEC® 25mm - PKM25SB

DARKFLEX tuš crevo 150cm - PGC150DF

Tuš ručica 3 Funkcije - PTR3C13D

Protok max. 8lit/min - WaterCare

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer

Minimalist design

Solid brass body

Dark black PVD finish

Wall assembly

Ceramic diverter 180°

Shower head 210x210mm - PTRUSP5D

CITEC®25 mm ceramic cartridge - PKM25SB

DARKFLEX shower hose 150cm - PGC150DF

3 Function hand shower - PTR3C13D

WaterCare - max flow rate 8lit/min

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

