

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# Thermo S2

PRODUCT CODE  
ŠIFRA PROIZVODA

**2T33101B**



### TEHNIČKI PODACI

Termostatska baterija  
Minimalistički dizajn  
Telo od mesinga  
Završna obrada - PVD Dark black  
Zidna montaža  
Keramički prebacivač CITEC® - PKM27TH  
Termostatski uložak AP - PKMTH2  
DARKFLEX tuš crevo 150cm - PGC150DF  
Tuš ručica 3 Funkcije - PTR3C13D

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Thermo regulation mixer  
Minimalist design  
Solid brass body  
Dark black PVD finish  
Wall assembly  
Ceramic diverter CITEC® - PKM27TH  
Theromostatic cartridge AP - PKMTH2  
DARKFLEX shower hose 150cm - PGC150DF  
3 Function hand shower - PTR3C13D

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

