

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# Thermo S2

PRODUCT CODE  
ŠIFRA PROIZVODA

**2T37101**



### TEHNIČKI PODACI

Termostatska baterija  
Minimalistički dizajn  
Telo od mesinga  
Hromirana završna obrada  
Zidna montaža  
Keramički gornji deo  
Termostatski uložak AP - PKMTH2  
SILVERFLEX tuš crevo 170cm - PGC170SF  
Tuš ručica 3 Funkcije - PTR3C13

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Thermo regulation mixer  
Minimalist design  
Solid brass body  
Chrome finish  
Wall assembly  
Ceramic head part  
Theromostatic cartridge AP - PKMTH2  
SILVERFLEX shower hose 170cm - PGC170SF  
3 Function hand shower - PTR3C13

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

